

<b>TECHNICAL</b>	<b>010</b>	
<b>DATA SHEET</b>	<b>MV ROUGE</b>	12/06/2001 Index : 0

## MARKING RESIN TAMPERPROOFING VARNISH

### 1/ DEFINITION

**MV ROUGE 010 is a marking resin specially formulated for the SPOTTING, CODING, MARKING of parts. It is recommended for tamper proofing of parts.**

### 2/ ADVANTAGES

Does not alter with time. Guarantee control. The film breaks when the screw, the bolt or others parts are being moved. Resistant to hot and cold water, to oils and petrol.

### 3/ APPLICATION FIELDS

Parts spotting.<sup>[1]</sup><sub>[SEP]</sub>  
Thanks to **MV ROUGE 010** it is possible to check if screws, bolts and rivets assemblies have been tampered with : computers, car industry, weapons, etc...

### 4/ TECHNICAL CHARACTERISTICS

Appearance.....	Viscous liquid <sup>[1]</sup> <sub>[SEP]</sub>
Colour .....	red <sup>[1]</sup> <sub>[SEP]</sub>
Operating temperature range.....	-40 to +200°C
Density.....	0.91 <sup>[1]</sup> <sub>[SEP]</sub>
Dust dry.....	maximum 1 minute
Viscosity.....	500-700 cP <sup>[1]</sup> <sub>[SEP]</sub>

**APPROVED** by car manufacturers.<sup>[1]</sup><sub>[SEP]</sub>

### 5/ INSTRUCTIONS FOR USE.

Ready for use. Application temperature : +5°C to +40°C.  
Apply the varnish in drops evenly to clean and dry surfaces.  
When the varnish is dry, it allows the marking of parts.

### 6/ STORAGE.

Minimum one year in its original packaging, well closed. Store in a dry place between 5°C and 25°C.

### 7/ HYGIENE AND SAFETY MEASURES.

Flammable. Avoid contact with eyes and skin. Keep out of reach of children.

### 8/ PACKAGING.

50 ml flasks by 6 (REF : 1010F3)

### 9/ ORAPI INFORMATION

Available in **GREEN** and **BLACK** with special orders of **96 flasks of 50 ml**

*ORAPI cannot know about every application for which the products are used nor their conditions of use. ORAPI cannot be held responsible for the suitability of the products for a given use or a specific purpose. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each specific case.*



**Plant and Headquarters**<sup>[1]</sup><sub>[SEP]</sub>

ZI EST- 12, Avenue Pierre Mendès France- BP40- 69511 Vaux en Velin Cedex- FRANCE<sup>[1]</sup><sub>[SEP]</sub>  
Tel (00. 33) 4. 78. 80. 46. 70- Fax (00.33). 4. 72.04.58.91 - Internet : [www.orapiweb.com](http://www.orapiweb.com)