



# ORAMETAL POCKET

## UNIVERSAL PUTTY WITH STEEL PARTICLES

### DEFINITION

Pre-dosed, mouldable epoxy putty for repairing all materials, especially metals.

### ADVANTAGES

- No waste; use only the amount required.
- Provides good bond on all materials, such as metals, PVC, wood, etc.
- Excellent resistance to oils, hydrocarbons, hot and cold water, acids and bases, alcohol, etc. very well.
- Possesses excellent, long-lasting stability. Does not rust.
- After complete drying, can be drilled, tapped, machined and painted.

### APPLICATION FIELDS

- Maintenance and repair in mechanics, wood-working and other applications.
- Sealing. Restoring and sealing leaks in piping.
- Use in gas and water tanks, radiators, sanitary or electric installations, pools, etc.
- Repairing pipes, faucets, drains, pumps, etc.
- Repairing tools, banisters, damaged threads, bodies of appliances, window frames, doors, etc.
- Ideal for all quick repair jobs.
- Must-have product in your toolbox.

### TECHNICAL CHARACTERISTICS

Aspect .....	Paste
Colour .....	Grey
Operating temperature .....	-40°C to +150°C
Hardness .....	80 Shore D
Useful life of mixed paste .....	<5 minutes
Complete drying time .....	30 minutes
Compression strength .....	84 N/mm <sup>2</sup>
Tensile strength .....	20 N/mm <sup>2</sup>
Complete drying .....	24 hours
Compression strength .....	84 MN/m <sup>2</sup> (12,000 psi)
VOC content .....	0%
Dielectric strength .....	400 Volts / mil
Electrical resistance	30,000 megaohms

**1/2**

**Manufacturing site and registered office**

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE  
 Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - [www.orapi-maintenance.com](http://www.orapi-maintenance.com)

ORAPI® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses."

## INSTRUCTIONS FOR USE

---

We recommend that you wear gloves while handling this product.

Cut off the amount of product you need for making the repair.

Knead for 1 minute until you obtain a homogenous paste.

Apply to clean and dry surface within 3 minutes of mixing the paste.

Application temperature: +5°C to +40°C.

For emergency repairs, paste can be used on wet and submerged surfaces.

However, we recommend you apply the putty on clean and dry surfaces.

## PACKAGING

---

115 g stick

Ref. 1221 D1

x 12

57 g stick

Ref. 1221 D3

x 24

**2/2**

**Manufacturing site and registered office**

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - [www.orapi-maintenance.com](http://www.orapi-maintenance.com)