

TECHNICAL DATA SHEET

TDS 503 / Index 02 - 03/06/2013





KLEANER

POWERFUL DRY GREASE REMOVER FOR PLASTICS

DEFINITION

Fast-acting dry grease remover for all surfaces. Does not degrade plastics.

ADVANTAGES

Cleans and evaporates quickly and completely.

Powerful spray; aerosol is equipped with a special nozzle.

Contains no chlorinated solvent; contains no solvent that is toxic to humans or to the environment.

Specially adapted for cleaning parts before bonding and painting, as well as cleaning printed circuit boards. Can be used on most plastics and fragile materials.

Leaves a pleasant fragrance.

KLEANER removes oil from all surfaces, dissolves greasy residue and removes harmful impurities easily thanks to its formula and its powerful jet.

KLEANER was specially formulated to replace TRICHLORETHANE 111.

APPLICATION FIELDS

Cleaning

- metal surfaces: mechanical parts, locks, engines, etc.
- synthetic surfaces: plastics (a preliminary test is recommended given the large variety of polymers).
- electrical and electronic devices, printed circuit boards, relays, micro-contacts (disconnected from power source).
- various mechanisms and piping where a clean and dry surface is essential.
- surfaces before applying inks, paints, glues, seams and crack detectors.

TECHNICAL CHARACTERISTICS

Aspect	transparent liquid
Odour	
Colour	colourless
Density (ASTM D4052)	0.720
Evaporation rate (ether = 1)	5
Kauri-Butanol Index	33

1/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com

ORAPI ® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses."



TECHNICAL DATA SHEET

TDS 503 / Index 02 - 03/06/2013

INSTRUCTIONS FOR USE

Spray the product onto the surface and allow to work for a few seconds. If necessary, wipe with a clean cloth. Repeat, if needed, for stubborn dirt or stains.

PACKAGING

650 ml aerosol

Ref. 4503 A4

x 12

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com