



MOB 30

MOUNTING PASTE WITH MOLYBDENUM DISULPHIDE HIGH MoS₂ CONCENTRATION LUBRIMOLY B100

DEFINITION

Mounting and anti-seizing paste with high concentration of molybdenum disulphide mixed with a very high quality mineral oil chosen for its synergistic effect with MoS₂.

ADVANTAGES

- Reduces friction and wear and tear.
- Delays the appearance of fretting.
- Facilitates the perfect running-in of machines by avoiding seizing.
- Facilitates dismantling of parts subject to temperatures of up to +450°C.
- Can be used to seal cable gland fittings.
- Compatible with all mineral substrates (oils, grease, etc.)

APPLICATION FIELDS

- Hinges, cams, runners, cable gland fittings.
- Cold fittings, bracing (significant reduction of effort).
- Pretreatment of precision mechanical assemblies (motor connecting rod, tool column, bending presses).
- Drilling and tapping special steels.
- Mounting any parts where later dismantling is needed, force fitting, keying, running-in, machining, pressing, etc.
- Greasing gas valves, shut-off valves, and metal, glass, and plastic sliding gates.

Never use on bearings that turn at over 300 rpm.

TECHNICAL CHARACTERISTICS

| | |
|--|-------------------------|
| Colour | Bluish grey |
| Density at 15°C kg/m ³ (FT 60-101)..... | 1040 |
| Drop point °C (NFT 60-102)..... | 150 |
| Worked penetration at 25°C after 60 strokes (NFT 60-132).... | 220/250 |
| MoS ₂ content | > 30% |
| Operating temperature | -60°C to +450°C (750°F) |

- 1/2 -
Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE
Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com

INSTRUCTIONS FOR USE

Very easy application with a brush or leather cloth on parts that have been carefully degreased.

PACKAGING

| | | |
|------------|--------------|------|
| 200 g tube | Ref. 3610 T4 | x 12 |
| 1 kg tin | Ref. 3610 B7 | x 6 |

Available as an aerosol with reference **603-PATE SPRAY** (ref 4603A4) NATO NSN certification 9150-14-421-1883

CERTIFICATION

- Certified by the FRENCH ARMY
- **NATO NSN** 9150-14-388-5966 (tube)
- **NATO NSN** 8030-14-544-1572 (tin)

- 2/2 -

Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com