



MOB 60

MOUNTING PASTE

WITH MOLYBDENUM DISULPHIDE

VERY HIGH CONCENTRATION OF MoS₂

DEFINITION

Mounting and anti-seizing paste with high concentration of molybdenum disulphide mixed with a very high quality mineral oil chosen for its synergistic effect with MoS₂.

ADVANTAGES

- Reduces friction and wear and tear.
- Delays the appearance of fretting.
- Facilitates the perfect running-in of machines by avoiding seizing.
- Facilitates dismantling of parts subject to temperatures of up to +450°C.
- Can be used to seal cable gland fittings.
- Compatible with all mineral substrates (oils, grease, etc.)

APPLICATION FIELDS

- Hinges, cams, runners, cable gland fittings.
- Cold fittings, bracing (significant reduction of effort).
- Pretreatment of precision mechanical assemblies (motor connecting rod, tool column, bending presses).
- Drilling and tapping special steels.
- Mounting any parts where later dismantling is needed, force fitting, keying, running-in, machining, pressing, etc.
- Greasing gas valves, shut-off valves, and metal, glass, and plastic sliding gates.
- Lubrication of clamping chucks.

Never use on bearings that turn at over 300 rpm.

TECHNICAL CHARACTERISTICS

Colour	Bluish grey
Density at 15°C kg/m ³ (FT 60-101).....	1300
Drop point °C (NFT 60-102).....	150
Worked penetration at 25°C after 60 strokes (NFT 60-132)....	220/250
MoS ₂ content	60%
Operating temperature	-60°C to +450°C (750°F)

- 1/2 -
Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE
Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com

INSTRUCTIONS FOR USE

Very easy application with a brush or leather cloth on parts that have been carefully degreased.

PACKAGING

200 g tube	Ref. 3611 T4	x 12
1 kg tin	Ref. 3611 B7	x 6

Available as an aerosol with reference **603-PATE SPRAY** (ref 4603A4) NATO NSN certification 9150-14-421-1883

CERTIFICATION

- **NSN** certification 8030 14 5092882
- Complies with standard MIL-PRF-83483
- **Aérospatiale** Reference PQ 81600
- Complies with **NATO S 722**, UK DEF STAN 80-81 Ed 3 Am 1

- 2/2 -

Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com