



CT 300

EXTREME CONDITIONS GREASE

INFUSIBLE

DEFINITION

Multi-purpose extreme pressure grease for lubricating machines working at high temperatures.

ADVANTAGES

Multi-purpose grease. Remarkable lubricating powers at high temperatures.
Very insoluble in water. No tendency to emulsify.
Easily 'pumpable'. Does not run even in case of overheating.
Excellent anti-oxidising and anti-corrosive properties.

APPLICATION FIELDS

Greasing main bearings, bearings, etc., working at high or ambient temperatures.
Glass industry, brickyards, steelworks, rolling mills, rubber, cardboard, paper, etc.

TECHNICAL CHARACTERISTICS

Colour	dark amber
Soap	inorganic
Operating temperature	-40°C to +210°C
Drop point	none
Worked penetration	250/295
Shell 4-ball EP welding test	315 kg
DN factor	> 100,000
ASTM D 1741 test (1,000 hours at 150°C)	no alteration
Creusot-Loire (1500 rpm, 16 hours, 180°C)	no alteration
Cl, F, S content	< 150 ppm

INSTRUCTIONS FOR USE

Degrease and dry parts for lubrication and apply to the parts to be treated.

PACKAGING

400 g cartridge	Ref. 3628 C4	x 12
1 kg tin	Ref. 3628 B7	x 6
5 kg bucket	Ref. 3628 S1	x 2
50 kg drum	Ref. 3628 O4	x 1

- 1/1 -

Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE
Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com