



GRAISSE A L'ARGENT (SILVER GREASE) CONDUCTIVE GREASE

ELECTROCONDUCTIVE

DEFINITION

Multi-purpose grease for lubricating mechanisms that require thermal and electrical conductivity.

ADVANTAGES

Multi-purpose grease. Remarkable lubricating power even under high pressure.
Excellent anti-oxidising and anti-corrosive properties.
Very good mechanical and thermal stability.
Conducts electricity.
Conducts heat.

APPLICATION FIELDS

For greasing, roller bearings, main bearings, contactors, connectors, etc.
Automotive industry, electronics, electrical work, etc.
Circuit breakers, selectors, switches, braids, etc.

TECHNICAL CHARACTERISTICS

Colour beige
Operating temperature -20°C to +250°C
Drop point > 250°C
Worked penetration 230/250
NLGI grade 3
Cl, F, S content < 200 ppm

INSTRUCTIONS FOR USE

Degrease and dry parts for lubrication and apply to the parts to be treated.

PACKAGING

250 g tin

Ref. 3634 B2

**- 1/1 -
Head office**

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE
Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com