

TECHNICAL DATA SHEET

TDS 640 / Index 02 - 14/03/2017

640



PATE BA

WHITE ANTI-SEIZING PASTE, + 1,000°C



DEFINITION

PATE BA is an assembly lubricant known as 'ceramic lubricant' used to assemble screwed parts, designed to withstand very high temperatures and used on ferrous and non-ferrous alloys.

This product complies with the requirements for use in the food and pharmaceutical industries.

ADVANTAGES

PATE BA provides effective protection against rust and contact corrosion.

It can be used to assemble all types of screwed parts, studs, threaded connections or seals.

The parts can be easily dismantled even after a long period (several years).

This is a clean and efficient lubricant.

SCOPE OF APPLICATION

PATE BA is particularly recommended for non-ferrous alloys for which other, more traditional pastes sometimes have chemical compatibility issues.

Treatment of tools and moulds in the plastic processing sector.

Anti-seizing paste for the food, pharmaceutical, paper, construction industries etc.

Can be used as a HEAT-CONDUCTING paste.

TECHNICAL CHARACTERISTICS

Colour	creamy white
Texture	smooth
Drop point	none
Penetration at 25°C (NFT 60-132)	300/340
NLGI grade	1
Density	1.6
Operating temperature	-25°C to +1000°C (dry lubrication)

1/2 Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com

ORAPI ® cannot know about every application for which the products are used nor their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each specific case. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.



TECHNICAL DATA SHEET

TDS 640 / Index 02 - 14/03/2017

INSTRUCTIONS FOR USE

Apply PATE BA with a brush or roller, prior to assembly, onto clean and degreased parts.

PACKAGING

200 g tube Ref. 3640 T4 x 12 1 kg tin Ref. 3640 B7 x 6

CERTIFICATIONS



InS H1 Registered No: 1797218

2/2 Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com