



SI 33

HIGH-QUALITY SILICONE GREASE

LITHIUM / SILICONE
Designed for HUMID ENVIRONMENTS

DEFINITION

Multi-purpose silicone grease for lubricating all types of mechanisms operating in humid and cold environments.

ADVANTAGES

- Anti-wear,
- Anti-corrosion,
- Withstands humid conditions and chemical environments,
- Withstands moderate loads,
- Suitable for high speeds,
- Its consistency is relatively stable when the temperature increases or decreases,
- Good resistance to extreme cold.

APPLICATION FIELDS

Ball bearings, needles and rollers, bearings, joints, works and public works equipment, handling and transport equipment, agricultural equipment and any mechanism requiring the use of a lubricant with enhanced water-repellent properties.

Lubricates gaskets.

Lubrication at ski resorts.

Lubrication in cold environments (refrigerators, freezers, etc.)

Plastic-on-plastic and plastic-on-metal lubrication.

Aeronautics, boating, automotive, etc.

TECHNICAL CHARACTERISTICS

Soap	Lithium
Operating temperature	from -60°C to +175°C
Freezing point	< -60°C
Colour	light beige
Drop point (NFT 60-102).....	205 °C
NLGI grade	2
Worked penetration 60 cPs (NFT 60-132)	240-280
Shell 4-ball EP welding test (ASTM D 2783)	> 260 kg
DN factor	200,000

- 1/2 -

Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com

INSTRUCTIONS FOR USE

Clean and degrease parts thoroughly before applying SI 33.

PACKAGING

100 g tube	Ref: 3652 T3	x 12
1 kg box	Ref: 3652 B7	x 6

- 2/2 -

Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com