


TECHNICAL DATA SHEET

TDS 677 / Index 02 - 03/06/2013





CT 10

EP 2 MULTI-PURPOSE LITHIUM GREASE

DEFINITION

CT 10 is a high quality, multi-purpose, universal 'lithium' grease. This EP2-class grease is far superior to so-called 'petroleum' greases.

ADVANTAGES

CT 10 contains anti-wear and anti-oxidisation additives; contains heavy metals-free anti-corrosion additives. CT 10 adheres well to metals and demonstrates good resistance to water and dust. Pumps well.

APPLICATION FIELDS

CT 10 is recommended for:

- Ball bearings, roller bearings, needles and rollers, main bearings, hinges, works and public works
 equipment, materials handling and transportation vehicles, agricultural equipment, and any
 mechanism subject to severe conditions;
- Mechanisms with fast-moving parts;
- Any mechanism carrying loads under impact;
- Humid and dusty environments;
- General lubrication for industrial-use, including in the automobile industry;
- Lubrication for frames, agricultural and civil engineering equipment.

TECHNICAL CHARACTERISTICS

Soap	Lithium
Viscosity of base oil	120 mm ² /s
Operating temperature	-25°C to +130°C
Colour	Dark amber
Drop point (NFT 60-102)	180°C
NLGI Grade	2
Worked penetration after 60 strokes (NFT 60-132)	265-295
Anti-rust performance (EMCOR) (NFT 60-135)	0 score
4-balls EP test (ASTM D 2596)	190 kg
DN Factor	>350.000

1/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com



TECHNICAL DATA SHEET

TDS 677 / Index 02 - 03/06/2013

INSTRUCTIONS FOR USE

Clean and degrease the parts before applying CT 10 grease. CT 10 can be applied using an aerosol or with a brush.

PACKAGING

400 g cartridge	Ref. 3677 C4	x 12
1 kg box	Ref. 3677 B7	x 6
5 kg bucket	Ref. 3677 S1	x 2
50 kg drum	Ref. 3677 O4	x 1
180 kg drum	Ref. 3677 U1	x 1

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com