



PROTOR BITUM ANTI-CORROSION PROTECTION SEALING

LONG-LASTING BITUMEN PROTECTION

DEFINITION

Anti-corrosion and sealing product providing a dry and flexible film for long-lasting protection.

ADVANTAGES

- Contains no chlorinated solvent; contains no toxic solvent.
- Demonstrates excellent performance in salt spray tests (> 800 hours).
- Quick drying (dust free in 2 hours). Could be paint after drying.
- Prevents humidity from penetrating on or in the treated surfaces.
- The film is highly resistant, even in extreme conditions: rain, wind, sea water, etc.
- Clean and remove with ORASOLV M1 solvent.
- This product is suitable for any parts, regardless of shape.

APPLICATION FIELDS

PROTOR BITUM is intended primarily for exterior protections: bridges, roofs, pylons, metal frames, cisterns, bodywork of public works or agricultural machinery, etc.

Waterproofing and protection for concrete or cement surfaces. Can be used on concrete, cement, metal, plastic, etc. Protects military equipment, harbour equipment, railway lines, etc.

TECHNICAL CHARACTERISTICS

Colour	black liquid
Flash point (ASTM D56)	35°C
Coverage	8 m ² /litre
Dry matter	63-67%
Dust free/dry	2 hours/12 hours
Température of use.....	60°C
Viscosity coupe FORD 6.....	55 à 60 secondes
Density	0.944
SNCF favourable toxicology assessment.....	No.1661 of 7/3/2013 and Code No. 02103535

INSTRUCTIONS FOR USE

Shake well before using. The product can be applied cold by soaking, with a brush or as a spray. Let the product dry before exposure to the elements. Served after each used.

PACKAGING

Aerosol 650 ml / 300	Ref. 47272 A4	x 12
5 kg bucket	Ref. 27272 S1	x 4

- 1 -

Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tel. +33 (0)4 74 40 20 20 - Fax +33 (0)4 74 40 20 21 www.orapi-maintenance.com