



# DEGRILUB

## DE-SEIZING LUBRICANT

### DEFINITION

De-seizing lubricant for all blocked or shiny mechanical parts.

### ADVANTAGES

DEGRILUB is a liquid product that wets extremely well and easily settles into seized parts to be loosened.  
DEGRILUB lubricates and eliminates noise.  
DEGRILUB counteracts humidity and provides anti-rust protection for metal surfaces.  
DEGRILUB is formulated from refined raw materials, contains no chlorinated solvents, and contains no solvents that are toxic to HUMANS or the ENVIRONMENT.  
DEGRILUB meets current legal requirements.  
DEGRILUB uses a gas propellant that does not harm the ozone layer (CO<sub>2</sub>).

### APPLICATION FIELDS

- **INDUSTRY:**

De-seizing threaded connections, blocked flanges, corroded or rusted nuts, and a variety of threads.  
Protecting metal surfaces (machine frames, chrome), and mechanisms exposed to the elements.  
Use on runners, and wood-working machines.

- **AUTOMOBILES and TRANSPORT**

Lubricating locks, hinges, springs and all inaccessible mechanisms.

- **COMMERCE**

Lubricating and protecting office equipment (drawers, hinges, sliding doors).

- **OTHER**

Use on door hinges, garage doors, various sliding door mechanisms.  
Insulating and protection against humidity; devices, lawn mowers, useful for do-it-yourself projects.  
Cleans and de-seizes hedge shear blades, various types of secateurs, bicycles, scooters, and cultivators.

1/2

**Manufacturing site and registered office**

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE  
Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - [www.orapi-maintenance.com](http://www.orapi-maintenance.com)

## TECHNICAL CHARACTERISTICS

---

Aspect .....	Transparent liquid
Odour .....	Pine
Colour .....	Light yellow
Density at 20°C .....	0.788
Flash point .....	>60°C

## INSTRUCTIONS FOR USE

---

Spray generously on parts to be loosened. Wait for the product to settle between surfaces.  
Release parts without forcing.  
Repeat application if parts remain blocked.

## PACKAGING

---

650 ml aerosol	ref. 4801 A4	x 12
5 L jerry-can	ref. 2801 J1	x 4
200 L drum	ref. 2801 U2	x 1

2/2

### Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE  
Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - [www.orapi-maintenance.com](http://www.orapi-maintenance.com)

ORAPI® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.