

TECHNICAL DATA SHEET

TDS 805 / Index 05 - 11/08/2015





WR + MULTI-PURPOSE DE-SEIZER PROTECTS DE-SEIZES LUBRICATES 5 FUNCTIONS – OVER 1,000 USES

DEFINITION

Multi-purpose water-repellent product with 5 main functions: eliminates water, cleans, protects, de-seizes and lubricates.

ADVANTAGES

A MULTI-PURPOSE product for PROFESSIONALS. Extremely weak surface tension and remarkable capillarity cause WR+ to settle underneath the water on metal surfaces and form an insulating film that protects from corrosion. WR+ settles into the smallest cracks and de-seizes rusted and blocked mechanisms. After WR+ has been applied, re-oxidation does not occur, even in extreme cases of corrosive environments (marine, road salt during winter months, etc.) WR+ lubricates without 'staining' or 'oiling'. For WR+ in aerosol form: Non-flammable and ecological gas propellant. Aérospatiale Reference PQ 81600: AIR 3634, NATO C 634, UK DEF STAN 68 10/2, FR DCSEA 231, US MIL L3150 B Amdt 2.

APPLICATION FIELDS

More than 1,000 known uses. Use in the automotive, HGV, public works, and aeronautics sectors (battery cable terminals, distributors, contactors, spark plugs); recreational boating and river boating equipment; precision mechanics and protection of micro-mechanisms; on all device surfaces to eliminate humidity; to protect firearms, bicycles, and fishing reels; and to protect plastic injection moulds.

TECHNICAL CHARACTERISTICS

Aspect	Transparent liquid
Odour	Pleasant
Density at 20°C (ASTM D 4052)	0.800
Flash point (ASTM D 56)	>30°C
Operating temperature	-60°C to +200°C

1/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com

ORAPI ® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability of a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.



INSTRUCTIONS FOR USE

<u>DESEIZER</u> Spray generously on blocked parts or place blocked parts in a bath. Wait for the product to settle between surfaces. Release parts. <u>LUBRICATE</u> Spray short bursts of product onto the mechanisms.

PACKAGING

270/200 ml aerosol 650 ml aerosol	ref. 4805 A8 - With special nozzle (see the picture) ref. 4805 A4 With special nozzle (see the picture)
1 L bottle	ref. 2805 i2
5 L jerrican	ref. 2805 J1
20 L jerrican	ref. 2805 O1
200 l drum	ref. 2805 U2



2/2 Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com

ORAPI ® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability or suitability or a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.