



FTS 60 EVANESCENT OIL

PRESSING, FOLDING, FORMING, etc.

DEFINITION

Evanescent (evaporating) oil for metal work: deformation, forming, folding and cutting even thick sheet metal (30/10 mm).

ADVANTAGES

- Does not stain metal
- Can be used for a variety of medium-sized operations: forming and cutting.
- Excellent anti-corrosion protection.
- Possesses considerable quenching ability.
- Improves the rate of zero-defect production.
- Can be used for working a variety of metals: ferrous and non-ferrous, aluminium, copper, cast iron, stainless steel and other alloys.
- Economical thanks to its effectiveness in a wide variety of situations.

APPLICATION FIELDS

Folding, cutting, bending, stamping, profiling, rolling, etc.

Manufacture of non-food packaging, such as tubs, tins, etc.

Manufacture of buckets, aerosols, burettes, etc.

Manufacture of air conditioning fins, vehicle parts, etc.

Also ideal for many industrial applications.

TECHNICAL CHARACTERISTICS

Colour	pale yellow
Density at 25°C - ASTM D 4052	0.77
Kinematic viscosity at 40°C - ASTM D 445	2.8 mPa.s
Flash point - ASTM D 56	> 61°C

INSTRUCTIONS FOR USE

Ready to use.

The evanescent lubricant can be applied drop by drop, by spraying or using felt.

PACKAGING

1 l container	ref. 2878 i2	x 1
5 l jerry can	ref. 2878 J1	x 1
20 l drum	ref. 2878 O1	x 1
200 l drum	ref. 2878 U2	x 1

1/1

Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com