



# LEAK DETECTOR

## GAS LEAK DETECTOR

MIL-PRF-25567 TYPE I  
NATO NSN 6850-14-422-4259  
NATO NSN 6850-14-514-7430

### DEFINITION

Detector of gas leakage.

### ADVANTAGES

Ecological.  
Biodegradable.  
Effective even for small leaks.  
Non-toxic.  
Non-corrosive.

### APPLICATION FIELDS

Piping, taps, connections, water works, pipes, valves.  
Natural gas vehicles feed system.  
Compressed air installations, gas-cylinder pressure gauges, refrigeration installations.  
LEAK DETECTOR contains no mineral oils and is suitable for use with all gases, including oxygen.

### TECHNICAL CHARACTERISTICS

Aspect .....	Liquid
Colour .....	Transparent light yellow
Flash point .....	None
Boiling point .....	>100°C
pH .....	8.5

### INSTRUCTIONS FOR USE

Spray on the area to be examined. Bubbles will form at the site of the leak.

1/2

**Manufacturing site and registered office**

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE  
Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - [www.orapi-maintenance.com](http://www.orapi-maintenance.com)

ORAPI® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.

## PACKAGING

---

650 ml aerosol	ref. 4952A4	x 12
1 L bottle	ref. 2952J1	x 4
60 L drum	ref. 2952O5	x 1

LEAK DETECTOR 952 packaged in 5 and 60 litres complies with EIGA / ICG doc78/08/E recommendations:

- product contains no ammonia.
- no ammonia content reduces the risk of SCC on copper-based alloys.
- product is water-based; residue has an autoignition temperature of > 100°C.
- product contains no halides.
- product is non-corrosive.
- product does not harm the environment.

See also:

ORAPI 745 - FORMULE GRAND FROID -30°C                      ref. 2745J1 in 5 L

**2/2**

### **Manufacturing site and registered office**

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE  
Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - [www.orapi-maintenance.com](http://www.orapi-maintenance.com)